

SPECIAL FEATURES

- ATPV = 14,6 cal/cm²
- high mechanical resistance
- inherent flame resistance
-

STANDARDS



EN 1149-5 protective clothing – electrostatic properties



EN 13034-6 protective clothing against liquid chemicals type 6



EN 61482-1-2 protection against thermal hazards of electric arc cl. 1



EN ISO 11611 protective clothing for use in welding Cl. 1 - A1



EN ISO 11612 protective clothing against heat and flame A1, B1, C1, E1, F1



FABRIC

- **Outer fabric 1** 35% Aramid, 30% Modacrylic, 25% Cotton, 9% Polyamide, 1% Other fibres
- **Fabric weight** 320 g/m²

FUTHER DETAILS

- Stand-up collar, concealed press stud band, 2 breast pockets with flap fastening, 2 side pockets with fastening and facing, 1 inside pocket, 1 inside mobile phone compartment with flap, cuffs with fastening

FARBE

royal blue/black

WASHING INSTRUCTIONS

- 60°C coloured wash (normal process)
- Do not bleach
- Mild drying process
- Iron at moderate temperature
- Do not dry clean



Suitable for industrial laundering - ISO 15797

BP® PARTNERSHIP

SIZE CHART

- 34/37n-50/52n; 33/37l-44/46l



FEEL THE DIFFERENCE

Bierbaum-Proenen. Since 1788.